



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.075.260.600.2PH	75	200	600	77	58	100	42
VC.075.260.650.2PH	75	200	650	92	61	105	44
VC.075.260.700.2PH	75	200	700	107	63	111	48
VC.075.260.750.2PH	75	200	750	123	65	116	51
VC.075.260.800.2PH	75	200	800	138	68	121	53
VC.075.260.850.2PH	75	200	850	153	70	127	57
VC.075.260.900.2PH	75	200	900	168	73	132	59
VC.075.260.950.2PH	75	200	950	184	75	138	63
VC.075.260.1000.2PH	75	200	1000	199	78	143	65
VC.075.260.1050.2PH	75	200	1050	214	80	149	69
VC.075.260.1100.2PH	75	200	1100	230	82	154	71
VC.075.260.1150.2PH	75	200	1150	245	85	158	74
VC.075.260.1200.2PH	75	200	1200	260	88	165	77
VC.075.260.1250.2PH	75	200	1250	276	90	170	80
VC.075.260.1300.2PH	75	200	1300	291	92	176	83
VC.075.260.1350.2PH	75	200	1350	306	95	181	86
VC.075.260.1400.2PH	75	200	1400	322	97	187	90
VC.075.260.1450.2PH	75	200	1450	337	100	192	92
VC.075.260.1500.2PH	75	200	1500	352	106	201	96
VC.075.260.1550.2PH	75	200	1550	368	108	206	98
VC.075.260.1600.2PH	75	200	1600	383	110	211	100
VC.075.260.1650.2PH	75	200	1650	398	113	217	104
VC.075.260.1700.2PH	75	200	1700	414	115	222	107
VC.075.260.1750.2PH	75	200	1750	429	118	228	110
VC.075.260.1800.2PH	75	200	1800	444	120	233	113
VC.075.260.1850.2PH	75	200	1850	460	123	239	116
VC.075.260.1900.2PH	75	200	1900	475	125	244	119
VC.075.260.1950.2PH	75	200	1950	490	128	249	121
VC.075.260.2000.2PH	75	200	2000	505	131	256	125
VC.075.260.2050.2PH	75	200	2050	521	134	261	127
VC.075.260.2100.2PH	75	200	2100	536	136	267	131
VC.075.260.2150.2PH	75	200	2150	551	139	272	133
VC.075.260.2200.2PH	75	200	2200	567	141	278	137
VC.075.260.2250.2PH	75	200	2250	582	144	283	139
VC.075.260.2300.2PH	75	200	2300	597	146	288	142
VC.075.260.2350.2PH	75	200	2350	613	148	294	146
VC.075.260.2400.2PH	75	200	2400	628	151	299	148
VC.075.260.2450.2PH	75	200	2450	643	157	308	152
VC.075.260.2500.2PH	75	200	2500	659	159	313	154
VC.075.260.2550.2PH	75	200	2550	674	162	319	158
VC.075.260.2600.2PH	75	200	2600	689	164	324	160
VC.075.260.2650.2PH	75	200	2650	705	166	330	164
VC.075.260.2700.2PH	75	200	2700	720	169	335	166
VC.075.260.2750.2PH	75	200	2750	735	172	340	169
VC.075.260.2800.2PH	75	200	2800	751	174	346	172
VC.075.260.2850.2PH	75	200	2850	766	176	351	175
VC.075.260.2900.2PH	75	200	2900	781	179	357	178
VC.075.260.2950.2PH	75	200	2950	797	181	362	181
VC.075.260.3000.2PH	75	200	3000	812	184	368	185