



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.075.300.600.2PH	75	300	600	82	55	91	36
VC.075.300.650.2PH	75	300	650	99	57	95	38
VC.075.300.700.2PH	75	300	700	115	59	101	42
VC.075.300.750.2PH	75	300	750	132	62	105	44
VC.075.300.800.2PH	75	300	800	148	64	110	46
VC.075.300.850.2PH	75	300	850	165	66	115	49
VC.075.300.900.2PH	75	300	900	181	68	119	51
VC.075.300.950.2PH	75	300	950	197	71	125	54
VC.075.300.1000.2PH	75	300	1000	214	73	129	56
VC.075.300.1050.2PH	75	300	1050	230	75	135	60
VC.075.300.1100.2PH	75	300	1100	247	77	139	62
VC.075.300.1150.2PH	75	300	1150	263	80	143	64
VC.075.300.1200.2PH	75	300	1200	280	82	149	67
VC.075.300.1250.2PH	75	300	1250	296	85	153	69
VC.075.300.1300.2PH	75	300	1300	313	87	159	72
VC.075.300.1350.2PH	75	300	1350	329	89	163	74
VC.075.300.1400.2PH	75	300	1400	346	91	169	77
VC.075.300.1450.2PH	75	300	1450	362	94	173	79
VC.075.300.1500.2PH	75	300	1500	379	99	182	83
VC.075.300.1550.2PH	75	300	1550	395	101	186	85
VC.075.300.1600.2PH	75	300	1600	411	104	190	87
VC.075.300.1650.2PH	75	300	1650	428	106	196	90
VC.075.300.1700.2PH	75	300	1700	444	108	200	92
VC.075.300.1750.2PH	75	300	1750	461	110	206	95
VC.075.300.1800.2PH	75	300	1800	477	113	210	97
VC.075.300.1850.2PH	75	300	1850	494	115	215	101
VC.075.300.1900.2PH	75	300	1900	510	117	220	103
VC.075.300.1950.2PH	75	300	1950	527	120	224	105
VC.075.300.2000.2PH	75	300	2000	543	123	231	108
VC.075.300.2050.2PH	75	300	2050	560	126	235	110
VC.075.300.2100.2PH	75	300	2100	576	128	241	113
VC.075.300.2150.2PH	75	300	2150	592	130	245	115
VC.075.300.2200.2PH	75	300	2200	609	132	251	118
VC.075.300.2250.2PH	75	300	2250	625	135	255	120
VC.075.300.2300.2PH	75	300	2300	642	137	259	122
VC.075.300.2350.2PH	75	300	2350	658	139	265	126
VC.075.300.2400.2PH	75	300	2400	675	141	269	128
VC.075.300.2450.2PH	75	300	2450	691	147	278	131
VC.075.300.2500.2PH	75	300	2500	708	149	282	133
VC.075.300.2550.2PH	75	300	2550	724	151	288	136
VC.075.300.2600.2PH	75	300	2600	741	154	292	138
VC.075.300.2650.2PH	75	300	2650	757	156	297	142
VC.075.300.2700.2PH	75	300	2700	773	158	302	144
VC.075.300.2750.2PH	75	300	2750	790	161	306	146
VC.075.300.2800.2PH	75	300	2800	806	163	312	149
VC.075.300.2850.2PH	75	300	2850	823	165	316	151
VC.075.300.2900.2PH	75	300	2900	839	168	322	154
VC.075.300.2950.2PH	75	300	2950	856	170	326	156
VC.075.300.3000.2PH	75	300	3000	872	172	331	159