



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.075.300.600.4PH	75	300	600	110	74	120	46
VC.075.300.650.4PH	75	300	650	132	78	127	48
VC.075.300.700.4PH	75	300	700	154	82	134	52
VC.075.300.750.4PH	75	300	750	176	86	141	55
VC.075.300.800.4PH	75	300	800	198	89	147	58
VC.075.300.850.4PH	75	300	850	220	93	155	62
VC.075.300.900.4PH	75	300	900	242	97	161	64
VC.075.300.950.4PH	75	300	950	264	101	169	68
VC.075.300.1000.4PH	75	300	1000	287	104	175	71
VC.075.300.1050.4PH	75	300	1050	309	108	183	75
VC.075.300.1100.4PH	75	300	1100	331	112	190	78
VC.075.300.1150.4PH	75	300	1150	353	116	196	80
VC.075.300.1200.4PH	75	300	1200	375	120	204	84
VC.075.300.1250.4PH	75	300	1250	397	124	211	87
VC.075.300.1300.4PH	75	300	1300	419	127	218	91
VC.075.300.1350.4PH	75	300	1350	441	131	225	94
VC.075.300.1400.4PH	75	300	1400	463	135	232	98
VC.075.300.1450.4PH	75	300	1450	485	139	239	100
VC.075.300.1500.4PH	75	300	1500	507	146	250	104
VC.075.300.1550.4PH	75	300	1550	529	150	257	107
VC.075.300.1600.4PH	75	300	1600	551	154	263	110
VC.075.300.1650.4PH	75	300	1650	573	157	271	114
VC.075.300.1700.4PH	75	300	1700	595	161	277	116
VC.075.300.1750.4PH	75	300	1750	617	165	285	120
VC.075.300.1800.4PH	75	300	1800	639	169	292	123
VC.075.300.1850.4PH	75	300	1850	661	172	299	127
VC.075.300.1900.4PH	75	300	1900	683	176	306	130
VC.075.300.1950.4PH	75	300	1950	705	180	313	132
VC.075.300.2000.4PH	75	300	2000	727	185	322	136
VC.075.300.2050.4PH	75	300	2050	749	189	328	139
VC.075.300.2100.4PH	75	300	2100	771	193	336	143
VC.075.300.2150.4PH	75	300	2150	793	197	342	145
VC.075.300.2200.4PH	75	300	2200	815	200	350	149
VC.075.300.2250.4PH	75	300	2250	838	204	356	152
VC.075.300.2300.4PH	75	300	2300	860	208	363	155
VC.075.300.2350.4PH	75	300	2350	882	212	370	159
VC.075.300.2400.4PH	75	300	2400	904	215	377	161
VC.075.300.2450.4PH	75	300	2450	926	223	388	165
VC.075.300.2500.4PH	75	300	2500	948	227	395	168
VC.075.300.2550.4PH	75	300	2550	970	231	403	172
VC.075.300.2600.4PH	75	300	2600	992	234	409	175
VC.075.300.2650.4PH	75	300	2650	1014	238	417	179
VC.075.300.2700.4PH	75	300	2700	1036	242	424	181
VC.075.300.2750.4PH	75	300	2750	1058	246	430	184
VC.075.300.2800.4PH	75	300	2800	1080	250	438	188
VC.075.300.2850.4PH	75	300	2850	1102	253	444	191
VC.075.300.2900.4PH	75	300	2900	1124	257	452	195
VC.075.300.2950.4PH	75	300	2950	1146	261	458	197
VC.075.300.3000.4PH	75	300	3000	1168	265	466	201