



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.090.200.600.2PH	90	200	600	84	58	94	36
VC.090.200.650.2PH	90	200	650	101	60	98	38
VC.090.200.700.2PH	90	200	700	117	62	104	42
VC.090.200.750.2PH	90	200	750	134	65	108	44
VC.090.200.800.2PH	90	200	800	151	67	113	46
VC.090.200.850.2PH	90	200	850	168	69	118	49
VC.090.200.900.2PH	90	200	900	184	72	123	51
VC.090.200.950.2PH	90	200	950	201	74	128	54
VC.090.200.1000.2PH	90	200	1000	218	76	133	56
VC.090.200.1050.2PH	90	200	1050	235	79	138	60
VC.090.200.1100.2PH	90	200	1100	251	81	143	62
VC.090.200.1150.2PH	90	200	1150	268	83	147	64
VC.090.200.1200.2PH	90	200	1200	285	86	153	67
VC.090.200.1250.2PH	90	200	1250	302	88	157	69
VC.090.200.1300.2PH	90	200	1300	318	91	163	72
VC.090.200.1350.2PH	90	200	1350	335	93	167	74
VC.090.200.1400.2PH	90	200	1400	352	95	173	77
VC.090.200.1450.2PH	90	200	1450	369	98	177	79
VC.090.200.1500.2PH	90	200	1500	385	103	186	83
VC.090.200.1550.2PH	90	200	1550	402	106	190	85
VC.090.200.1600.2PH	90	200	1600	419	108	195	87
VC.090.200.1650.2PH	90	200	1650	436	110	200	90
VC.090.200.1700.2PH	90	200	1700	452	113	205	92
VC.090.200.1750.2PH	90	200	1750	469	115	210	95
VC.090.200.1800.2PH	90	200	1800	486	117	215	97
VC.090.200.1850.2PH	90	200	1850	503	120	220	101
VC.090.200.1900.2PH	90	200	1900	519	122	225	103
VC.090.200.1950.2PH	90	200	1950	536	125	229	105
VC.090.200.2000.2PH	90	200	2000	553	128	236	108
VC.090.200.2050.2PH	90	200	2050	570	131	241	110
VC.090.200.2100.2PH	90	200	2100	586	133	246	113
VC.090.200.2150.2PH	90	200	2150	603	135	251	115
VC.090.200.2200.2PH	90	200	2200	620	138	256	118
VC.090.200.2250.2PH	90	200	2250	637	140	260	120
VC.090.200.2300.2PH	90	200	2300	653	142	265	122
VC.090.200.2350.2PH	90	200	2350	670	145	270	126
VC.090.200.2400.2PH	90	200	2400	687	147	275	128
VC.090.200.2450.2PH	90	200	2450	704	153	284	131
VC.090.200.2500.2PH	90	200	2500	720	155	288	133
VC.090.200.2550.2PH	90	200	2550	737	157	294	136
VC.090.200.2600.2PH	90	200	2600	754	160	298	138
VC.090.200.2650.2PH	90	200	2650	771	162	304	142
VC.090.200.2700.2PH	90	200	2700	787	165	308	144
VC.090.200.2750.2PH	90	200	2750	804	167	312	146
VC.090.200.2800.2PH	90	200	2800	821	169	318	149
VC.090.200.2850.2PH	90	200	2850	838	172	322	151
VC.090.200.2900.2PH	90	200	2900	854	174	328	154
VC.090.200.2950.2PH	90	200	2950	871	176	332	156
VC.090.200.3000.2PH	90	200	3000	888	186	345	159