



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.090.260.600.2PH	90	260	600	111	61	103	42
VC.090.260.650.2PH	90	260	650	133	63	108	44
VC.090.260.700.2PH	90	260	700	155	66	114	48
VC.090.260.750.2PH	90	260	750	178	68	119	51
VC.090.260.800.2PH	90	260	800	200	71	124	53
VC.090.260.850.2PH	90	260	850	222	74	130	57
VC.090.260.900.2PH	90	260	900	244	76	135	59
VC.090.260.950.2PH	90	260	950	266	79	141	63
VC.090.260.1000.2PH	90	260	1000	289	81	146	65
VC.090.260.1050.2PH	90	260	1050	311	84	152	69
VC.090.260.1100.2PH	90	260	1100	333	86	157	71
VC.090.260.1150.2PH	90	260	1150	355	89	162	74
VC.090.260.1200.2PH	90	260	1200	377	91	169	77
VC.090.260.1250.2PH	90	260	1250	400	94	174	80
VC.090.260.1300.2PH	90	260	1300	422	96	180	83
VC.090.260.1350.2PH	90	260	1350	444	99	185	86
VC.090.260.1400.2PH	90	260	1400	466	101	191	90
VC.090.260.1450.2PH	90	260	1450	488	104	196	92
VC.090.260.1500.2PH	90	260	1500	511	110	205	96
VC.090.260.1550.2PH	90	260	1550	533	112	210	98
VC.090.260.1600.2PH	90	260	1600	555	115	215	100
VC.090.260.1650.2PH	90	260	1650	577	117	222	104
VC.090.260.1700.2PH	90	260	1700	599	120	226	107
VC.090.260.1750.2PH	90	260	1750	622	122	233	110
VC.090.260.1800.2PH	90	260	1800	644	125	238	113
VC.090.260.1850.2PH	90	260	1850	666	127	244	116
VC.090.260.1900.2PH	90	260	1900	688	130	249	119
VC.090.260.1950.2PH	90	260	1950	710	133	254	121
VC.090.260.2000.2PH	90	260	2000	733	137	261	125
VC.090.260.2050.2PH	90	260	2050	755	139	266	127
VC.090.260.2100.2PH	90	260	2100	777	142	273	131
VC.090.260.2150.2PH	90	260	2150	799	144	277	133
VC.090.260.2200.2PH	90	260	2200	821	147	284	137
VC.090.260.2250.2PH	90	260	2250	844	149	289	139
VC.090.260.2300.2PH	90	260	2300	866	152	293	142
VC.090.260.2350.2PH	90	260	2350	888	154	300	146
VC.090.260.2400.2PH	90	260	2400	910	157	305	148
VC.090.260.2450.2PH	90	260	2450	932	163	314	152
VC.090.260.2500.2PH	90	260	2500	955	165	319	154
VC.090.260.2550.2PH	90	260	2550	977	168	325	158
VC.090.260.2600.2PH	90	260	2600	999	170	330	160
VC.090.260.2650.2PH	90	260	2650	1021	173	336	164
VC.090.260.2700.2PH	90	260	2700	1043	175	342	166
VC.090.260.2750.2PH	90	260	2750	1066	178	347	169
VC.090.260.2800.2PH	90	260	2800	1088	180	353	172
VC.090.260.2850.2PH	90	260	2850	1110	183	358	175
VC.090.260.2900.2PH	90	260	2900	1132	185	364	178
VC.090.260.2950.2PH	90	260	2950	1154	188	369	181
VC.090.260.3000.2PH	90	260	3000	1177	197	382	185