



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.090.300.600.2PH	90	300	600	125	64	110	46
VC.090.300.650.2PH	90	300	650	150	67	115	48
VC.090.300.700.2PH	90	300	700	175	69	122	52
VC.090.300.750.2PH	90	300	750	199	72	127	55
VC.090.300.800.2PH	90	300	800	224	74	132	58
VC.090.300.850.2PH	90	300	850	249	77	139	62
VC.090.300.900.2PH	90	300	900	274	80	144	64
VC.090.300.950.2PH	90	300	950	299	82	151	68
VC.090.300.1000.2PH	90	300	1000	324	85	156	71
VC.090.300.1050.2PH	90	300	1050	349	87	162	75
VC.090.300.1100.2PH	90	300	1100	374	90	168	78
VC.090.300.1150.2PH	90	300	1150	399	93	173	80
VC.090.300.1200.2PH	90	300	1200	424	96	180	84
VC.090.300.1250.2PH	90	300	1250	449	98	185	87
VC.090.300.1300.2PH	90	300	1300	474	101	192	91
VC.090.300.1350.2PH	90	300	1350	499	103	197	94
VC.090.300.1400.2PH	90	300	1400	524	106	204	98
VC.090.300.1450.2PH	90	300	1450	549	109	209	100
VC.090.300.1500.2PH	90	300	1500	574	115	219	104
VC.090.300.1550.2PH	90	300	1550	598	118	225	107
VC.090.300.1600.2PH	90	300	1600	623	120	230	110
VC.090.300.1650.2PH	90	300	1650	648	123	237	114
VC.090.300.1700.2PH	90	300	1700	673	126	242	116
VC.090.300.1750.2PH	90	300	1750	698	128	249	120
VC.090.300.1800.2PH	90	300	1800	723	131	254	123
VC.090.300.1850.2PH	90	300	1850	748	134	260	127
VC.090.300.1900.2PH	90	300	1900	773	136	266	130
VC.090.300.1950.2PH	90	300	1950	798	139	271	132
VC.090.300.2000.2PH	90	300	2000	823	143	279	136
VC.090.300.2050.2PH	90	300	2050	848	146	285	139
VC.090.300.2100.2PH	90	300	2100	873	148	291	143
VC.090.300.2150.2PH	90	300	2150	898	151	296	145
VC.090.300.2200.2PH	90	300	2200	923	154	303	149
VC.090.300.2250.2PH	90	300	2250	948	156	308	152
VC.090.300.2300.2PH	90	300	2300	972	159	314	155
VC.090.300.2350.2PH	90	300	2350	997	161	320	159
VC.090.300.2400.2PH	90	300	2400	1022	164	325	161
VC.090.300.2450.2PH	90	300	2450	1047	171	336	165
VC.090.300.2500.2PH	90	300	2500	1072	173	341	168
VC.090.300.2550.2PH	90	300	2550	1097	176	348	172
VC.090.300.2600.2PH	90	300	2600	1122	178	353	175
VC.090.300.2650.2PH	90	300	2650	1147	181	360	179
VC.090.300.2700.2PH	90	300	2700	1172	184	365	181
VC.090.300.2750.2PH	90	300	2750	1197	187	371	184
VC.090.300.2800.2PH	90	300	2800	1222	189	377	188
VC.090.300.2850.2PH	90	300	2850	1247	192	382	191
VC.090.300.2900.2PH	90	300	2900	1272	194	389	195
VC.090.300.2950.2PH	90	300	2950	1297	197	394	197
VC.090.300.3000.2PH	90	300	3000	1322	206	408	201