



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.090.300.600.4PH	90	300	600	145	77	122	46
VC.090.300.650.4PH	90	300	650	174	81	129	48
VC.090.300.700.4PH	90	300	700	203	85	137	52
VC.090.300.750.4PH	90	300	750	232	89	144	55
VC.090.300.800.4PH	90	300	800	261	92	150	58
VC.090.300.850.4PH	90	300	850	290	96	158	62
VC.090.300.900.4PH	90	300	900	319	100	164	64
VC.090.300.950.4PH	90	300	950	348	104	172	68
VC.090.300.1000.4PH	90	300	1000	377	108	179	71
VC.090.300.1050.4PH	90	300	1050	406	111	186	75
VC.090.300.1100.4PH	90	300	1100	435	115	193	78
VC.090.300.1150.4PH	90	300	1150	464	119	199	80
VC.090.300.1200.4PH	90	300	1200	493	123	208	84
VC.090.300.1250.4PH	90	300	1250	522	127	214	87
VC.090.300.1300.4PH	90	300	1300	551	131	222	91
VC.090.300.1350.4PH	90	300	1350	580	135	229	94
VC.090.300.1400.4PH	90	300	1400	609	139	236	98
VC.090.300.1450.4PH	90	300	1450	638	143	243	100
VC.090.300.1500.4PH	90	300	1500	667	150	255	104
VC.090.300.1550.4PH	90	300	1550	696	154	261	107
VC.090.300.1600.4PH	90	300	1600	725	158	268	110
VC.090.300.1650.4PH	90	300	1650	754	162	275	114
VC.090.300.1700.4PH	90	300	1700	783	166	282	116
VC.090.300.1750.4PH	90	300	1750	812	169	290	120
VC.090.300.1800.4PH	90	300	1800	841	173	296	123
VC.090.300.1850.4PH	90	300	1850	870	177	304	127
VC.090.300.1900.4PH	90	300	1900	899	181	310	130
VC.090.300.1950.4PH	90	300	1950	928	185	317	132
VC.090.300.2000.4PH	90	300	2000	957	190	326	136
VC.090.300.2050.4PH	90	300	2050	986	194	333	139
VC.090.300.2100.4PH	90	300	2100	1015	198	341	143
VC.090.300.2150.4PH	90	300	2150	1044	202	347	145
VC.090.300.2200.4PH	90	300	2200	1073	206	355	149
VC.090.300.2250.4PH	90	300	2250	1102	209	362	152
VC.090.300.2300.4PH	90	300	2300	1131	213	368	155
VC.090.300.2350.4PH	90	300	2350	1160	217	376	159
VC.090.300.2400.4PH	90	300	2400	1189	221	382	161
VC.090.300.2450.4PH	90	300	2450	1218	229	394	165
VC.090.300.2500.4PH	90	300	2500	1247	232	401	168
VC.090.300.2550.4PH	90	300	2550	1276	236	408	172
VC.090.300.2600.4PH	90	300	2600	1305	240	415	175
VC.090.300.2650.4PH	90	300	2650	1334	244	423	179
VC.090.300.2700.4PH	90	300	2700	1363	248	430	181
VC.090.300.2750.4PH	90	300	2750	1392	252	436	184
VC.090.300.2800.4PH	90	300	2800	1421	256	444	188
VC.090.300.2850.4PH	90	300	2850	1450	260	450	191
VC.090.300.2900.4PH	90	300	2900	1479	263	458	195
VC.090.300.2950.4PH	90	300	2950	1508	267	465	197
VC.090.300.3000.4PH	90	300	3000	1537	278	479	201