



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.090.400.600.4PH	90	400	600	169	84	139	55
VC.090.400.650.4PH	90	400	650	203	88	146	58
VC.090.400.700.4PH	90	400	700	237	92	155	63
VC.090.400.750.4PH	90	400	750	271	96	162	66
VC.090.400.800.4PH	90	400	800	305	100	170	70
VC.090.400.850.4PH	90	400	850	339	104	179	74
VC.090.400.900.4PH	90	400	900	373	108	186	78
VC.090.400.950.4PH	90	400	950	406	112	195	82
VC.090.400.1000.4PH	90	400	1000	440	116	202	86
VC.090.400.1050.4PH	90	400	1050	474	121	211	90
VC.090.400.1100.4PH	90	400	1100	508	125	218	94
VC.090.400.1150.4PH	90	400	1150	542	129	226	97
VC.090.400.1200.4PH	90	400	1200	576	133	235	102
VC.090.400.1250.4PH	90	400	1250	610	137	243	105
VC.090.400.1300.4PH	90	400	1300	644	141	251	110
VC.090.400.1350.4PH	90	400	1350	677	146	259	113
VC.090.400.1400.4PH	90	400	1400	711	150	267	118
VC.090.400.1450.4PH	90	400	1450	745	154	275	121
VC.090.400.1500.4PH	90	400	1500	779	163	288	126
VC.090.400.1550.4PH	90	400	1550	813	167	296	129
VC.090.400.1600.4PH	90	400	1600	847	171	303	133
VC.090.400.1650.4PH	90	400	1650	881	175	312	137
VC.090.400.1700.4PH	90	400	1700	915	179	319	141
VC.090.400.1750.4PH	90	400	1750	948	183	328	145
VC.090.400.1800.4PH	90	400	1800	982	187	336	149
VC.090.400.1850.4PH	90	400	1850	1016	191	344	153
VC.090.400.1900.4PH	90	400	1900	1050	195	352	157
VC.090.400.1950.4PH	90	400	1950	1084	200	360	160
VC.090.400.2000.4PH	90	400	2000	1118	205	370	165
VC.090.400.2050.4PH	90	400	2050	1152	209	377	168
VC.090.400.2100.4PH	90	400	2100	1186	213	386	173
VC.090.400.2150.4PH	90	400	2150	1219	218	393	176
VC.090.400.2200.4PH	90	400	2200	1253	222	402	181
VC.090.400.2250.4PH	90	400	2250	1287	226	410	184
VC.090.400.2300.4PH	90	400	2300	1321	230	417	187
VC.090.400.2350.4PH	90	400	2350	1355	234	426	192
VC.090.400.2400.4PH	90	400	2400	1389	238	433	195
VC.090.400.2450.4PH	90	400	2450	1423	247	447	200
VC.090.400.2500.4PH	90	400	2500	1457	251	454	203
VC.090.400.2550.4PH	90	400	2550	1490	255	463	208
VC.090.400.2600.4PH	90	400	2600	1524	259	470	211
VC.090.400.2650.4PH	90	400	2650	1558	263	479	216
VC.090.400.2700.4PH	90	400	2700	1592	268	487	219
VC.090.400.2750.4PH	90	400	2750	1626	272	494	223
VC.090.400.2800.4PH	90	400	2800	1660	276	503	227
VC.090.400.2850.4PH	90	400	2850	1694	280	511	231
VC.090.400.2900.4PH	90	400	2900	1728	284	519	235
VC.090.400.2950.4PH	90	400	2950	1761	288	527	239
VC.090.400.3000.4PH	90	400	3000	1795	299	542	243