



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.075.200.600.2PH	75	200	600	59	55	91	36
VC.075.200.650.2PH	75	200	650	71	57	95	38
VC.075.200.700.2PH	75	200	700	83	59	101	42
VC.075.200.750.2PH	75	200	750	95	62	105	44
VC.075.200.800.2PH	75	200	800	107	64	110	46
VC.075.200.850.2PH	75	200	850	119	66	115	49
VC.075.200.900.2PH	75	200	900	131	68	119	51
VC.075.200.950.2PH	75	200	950	143	71	125	54
VC.075.200.1000.2PH	75	200	1000	155	73	129	56
VC.075.200.1050.2PH	75	200	1050	166	75	135	60
VC.075.200.1100.2PH	75	200	1100	178	77	139	62
VC.075.200.1150.2PH	75	200	1150	190	80	143	64
VC.075.200.1200.2PH	75	200	1200	202	82	149	67
VC.075.200.1250.2PH	75	200	1250	214	85	153	69
VC.075.200.1300.2PH	75	200	1300	226	87	159	72
VC.075.200.1350.2PH	75	200	1350	238	89	163	74
VC.075.200.1400.2PH	75	200	1400	250	91	169	77
VC.075.200.1450.2PH	75	200	1450	262	94	173	79
VC.075.200.1500.2PH	75	200	1500	274	99	182	83
VC.075.200.1550.2PH	75	200	1550	285	101	186	85
VC.075.200.1600.2PH	75	200	1600	297	104	190	87
VC.075.200.1650.2PH	75	200	1650	309	106	196	90
VC.075.200.1700.2PH	75	200	1700	321	108	200	92
VC.075.200.1750.2PH	75	200	1750	333	110	206	95
VC.075.200.1800.2PH	75	200	1800	345	113	210	97
VC.075.200.1850.2PH	75	200	1850	357	115	215	101
VC.075.200.1900.2PH	75	200	1900	369	117	220	103
VC.075.200.1950.2PH	75	200	1950	381	120	224	105
VC.075.200.2000.2PH	75	200	2000	392	123	231	108
VC.075.200.2050.2PH	75	200	2050	404	126	235	110
VC.075.200.2100.2PH	75	200	2100	416	128	241	113
VC.075.200.2150.2PH	75	200	2150	428	130	245	115
VC.075.200.2200.2PH	75	200	2200	440	132	251	118
VC.075.200.2250.2PH	75	200	2250	452	135	255	120
VC.075.200.2300.2PH	75	200	2300	464	137	259	122
VC.075.200.2350.2PH	75	200	2350	476	139	265	126
VC.075.200.2400.2PH	75	200	2400	488	141	269	128
VC.075.200.2450.2PH	75	200	2450	499	147	278	131
VC.075.200.2500.2PH	75	200	2500	511	149	282	133
VC.075.200.2550.2PH	75	200	2550	523	151	288	136
VC.075.200.2600.2PH	75	200	2600	535	154	292	138
VC.075.200.2650.2PH	75	200	2650	547	156	297	142
VC.075.200.2700.2PH	75	200	2700	559	158	302	144
VC.075.200.2750.2PH	75	200	2750	571	161	306	146
VC.075.200.2800.2PH	75	200	2800	583	163	312	149
VC.075.200.2850.2PH	75	200	2850	595	165	316	151
VC.075.200.2900.2PH	75	200	2900	607	168	322	154
VC.075.200.2950.2PH	75	200	2950	618	170	326	156
VC.075.200.3000.2PH	75	200	3000	630	172	331	159