



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.110.200.600.2PH	110	200	600	105	56	93	36
VC.110.200.650.2PH	110	200	650	126	59	97	38
VC.110.200.700.2PH	110	200	700	147	61	103	42
VC.110.200.750.2PH	110	200	750	168	63	107	44
VC.110.200.800.2PH	110	200	800	189	66	112	46
VC.110.200.850.2PH	110	200	850	210	68	117	49
VC.110.200.900.2PH	110	200	900	231	70	121	51
VC.110.200.950.2PH	110	200	950	252	77	131	54
VC.110.200.1000.2PH	110	200	1000	273	79	135	56
VC.110.200.1050.2PH	110	200	1050	294	82	141	60
VC.110.200.1100.2PH	110	200	1100	315	84	146	62
VC.110.200.1150.2PH	110	200	1150	336	86	150	64
VC.110.200.1200.2PH	110	200	1200	357	89	156	67
VC.110.200.1250.2PH	110	200	1250	378	92	160	69
VC.110.200.1300.2PH	110	200	1300	399	94	166	72
VC.110.200.1350.2PH	110	200	1350	420	97	171	74
VC.110.200.1400.2PH	110	200	1400	441	99	176	77
VC.110.200.1450.2PH	110	200	1450	462	101	181	79
VC.110.200.1500.2PH	110	200	1500	483	107	190	83
VC.110.200.1550.2PH	110	200	1550	504	110	194	85
VC.110.200.1600.2PH	110	200	1600	525	112	199	87
VC.110.200.1650.2PH	110	200	1650	546	115	204	90
VC.110.200.1700.2PH	110	200	1700	567	117	209	92
VC.110.200.1750.2PH	110	200	1750	588	119	215	95
VC.110.200.1800.2PH	110	200	1800	609	122	219	97
VC.110.200.1850.2PH	110	200	1850	630	124	225	101
VC.110.200.1900.2PH	110	200	1900	651	127	229	103
VC.110.200.1950.2PH	110	200	1950	672	130	234	105
VC.110.200.2000.2PH	110	200	2000	693	133	241	108
VC.110.200.2050.2PH	110	200	2050	714	136	246	110
VC.110.200.2100.2PH	110	200	2100	735	138	251	113
VC.110.200.2150.2PH	110	200	2150	756	141	256	115
VC.110.200.2200.2PH	110	200	2200	777	143	262	118
VC.110.200.2250.2PH	110	200	2250	798	146	266	120
VC.110.200.2300.2PH	110	200	2300	819	148	270	122
VC.110.200.2350.2PH	110	200	2350	840	150	276	126
VC.110.200.2400.2PH	110	200	2400	861	153	281	128
VC.110.200.2450.2PH	110	200	2450	882	159	290	131
VC.110.200.2500.2PH	110	200	2500	903	161	294	133
VC.110.200.2550.2PH	110	200	2550	924	164	300	136
VC.110.200.2600.2PH	110	200	2600	945	166	304	138
VC.110.200.2650.2PH	110	200	2650	966	168	310	142
VC.110.200.2700.2PH	110	200	2700	987	171	315	144
VC.110.200.2750.2PH	110	200	2750	1008	174	319	146
VC.110.200.2800.2PH	110	200	2800	1029	176	325	149
VC.110.200.2850.2PH	110	200	2850	1050	179	329	151
VC.110.200.2900.2PH	110	200	2900	1071	181	335	154
VC.110.200.2950.2PH	110	200	2950	1092	183	340	156
VC.110.200.3000.2PH	110	200	3000	1113	193	352	159