



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.110.260.600.2PH	110	260	600	133	63	105	42
VC.110.260.650.2PH	110	260	650	159	66	110	44
VC.110.260.700.2PH	110	260	700	186	68	116	48
VC.110.260.750.2PH	110	260	750	212	71	121	51
VC.110.260.800.2PH	110	260	800	239	74	126	53
VC.110.260.850.2PH	110	260	850	265	76	133	57
VC.110.260.900.2PH	110	260	900	292	79	138	59
VC.110.260.950.2PH	110	260	950	318	81	144	63
VC.110.260.1000.2PH	110	260	1000	345	84	149	65
VC.110.260.1050.2PH	110	260	1050	372	87	155	69
VC.110.260.1100.2PH	110	260	1100	398	89	160	71
VC.110.260.1150.2PH	110	260	1150	425	92	165	74
VC.110.260.1200.2PH	110	260	1200	451	95	172	77
VC.110.260.1250.2PH	110	260	1250	478	97	177	80
VC.110.260.1300.2PH	110	260	1300	504	100	183	83
VC.110.260.1350.2PH	110	260	1350	531	103	188	86
VC.110.260.1400.2PH	110	260	1400	557	105	195	90
VC.110.260.1450.2PH	110	260	1450	584	108	200	92
VC.110.260.1500.2PH	110	260	1500	610	114	210	96
VC.110.260.1550.2PH	110	260	1550	637	117	215	98
VC.110.260.1600.2PH	110	260	1600	664	119	220	100
VC.110.260.1650.2PH	110	260	1650	690	122	226	104
VC.110.260.1700.2PH	110	260	1700	717	124	231	107
VC.110.260.1750.2PH	110	260	1750	743	127	237	110
VC.110.260.1800.2PH	110	260	1800	770	130	242	113
VC.110.260.1850.2PH	110	260	1850	796	132	249	116
VC.110.260.1900.2PH	110	260	1900	823	135	254	119
VC.110.260.1950.2PH	110	260	1950	849	138	259	121
VC.110.260.2000.2PH	110	260	2000	876	142	267	125
VC.110.260.2050.2PH	110	260	2050	902	144	272	127
VC.110.260.2100.2PH	110	260	2100	929	147	278	131
VC.110.260.2150.2PH	110	260	2150	955	150	283	133
VC.110.260.2200.2PH	110	260	2200	982	152	289	137
VC.110.260.2250.2PH	110	260	2250	1009	155	294	139
VC.110.260.2300.2PH	110	260	2300	1035	157	299	142
VC.110.260.2350.2PH	110	260	2350	1062	160	306	146
VC.110.260.2400.2PH	110	260	2400	1088	163	311	148
VC.110.260.2450.2PH	110	260	2450	1115	169	321	152
VC.110.260.2500.2PH	110	260	2500	1141	171	326	154
VC.110.260.2550.2PH	110	260	2550	1168	174	332	158
VC.110.260.2600.2PH	110	260	2600	1194	177	337	160
VC.110.260.2650.2PH	110	260	2650	1221	179	343	164
VC.110.260.2700.2PH	110	260	2700	1247	182	348	166
VC.110.260.2750.2PH	110	260	2750	1274	185	353	169
VC.110.260.2800.2PH	110	260	2800	1301	187	360	172
VC.110.260.2850.2PH	110	260	2850	1327	190	365	175
VC.110.260.2900.2PH	110	260	2900	1354	193	371	178
VC.110.260.2950.2PH	110	260	2950	1380	195	376	181
VC.110.260.3000.2PH	110	260	3000	1407	205	389	185