



Article of convector	Height	Width	Length	Heat output in a (90°/70°/20°), W.	Convector without the grille and frame	Convector with aluminum, natural Oak grille and frame	Aluminum, natural Oak grille and frame
VC.110.400.600.4PH	110	400	600	205	86	141	55
VC.110.400.650.4PH	110	400	650	246	90	149	58
VC.110.400.700.4PH	110	400	700	288	95	158	63
VC.110.400.750.4PH	110	400	750	329	99	165	66
VC.110.400.800.4PH	110	400	800	370	103	173	70
VC.110.400.850.4PH	110	400	850	411	107	182	74
VC.110.400.900.4PH	110	400	900	452	111	189	78
VC.110.400.950.4PH	110	400	950	493	116	198	82
VC.110.400.1000.4PH	110	400	1000	534	120	206	86
VC.110.400.1050.4PH	110	400	1050	575	124	214	90
VC.110.400.1100.4PH	110	400	1100	616	128	222	94
VC.110.400.1150.4PH	110	400	1150	657	132	230	97
VC.110.400.1200.4PH	110	400	1200	698	137	239	102
VC.110.400.1250.4PH	110	400	1250	739	141	246	105
VC.110.400.1300.4PH	110	400	1300	780	145	255	110
VC.110.400.1350.4PH	110	400	1350	822	150	263	113
VC.110.400.1400.4PH	110	400	1400	863	154	272	118
VC.110.400.1450.4PH	110	400	1450	904	158	279	121
VC.110.400.1500.4PH	110	400	1500	945	167	293	126
VC.110.400.1550.4PH	110	400	1550	986	171	301	129
VC.110.400.1600.4PH	110	400	1600	1027	176	308	133
VC.110.400.1650.4PH	110	400	1650	1068	180	317	137
VC.110.400.1700.4PH	110	400	1700	1109	184	324	141
VC.110.400.1750.4PH	110	400	1750	1150	188	333	145
VC.110.400.1800.4PH	110	400	1800	1191	192	341	149
VC.110.400.1850.4PH	110	400	1850	1232	197	350	153
VC.110.400.1900.4PH	110	400	1900	1273	201	357	157
VC.110.400.1950.4PH	110	400	1950	1314	205	365	160
VC.110.400.2000.4PH	110	400	2000	1355	211	375	165
VC.110.400.2050.4PH	110	400	2050	1397	215	383	168
VC.110.400.2100.4PH	110	400	2100	1438	219	392	173
VC.110.400.2150.4PH	110	400	2150	1479	224	399	176
VC.110.400.2200.4PH	110	400	2200	1520	228	408	181
VC.110.400.2250.4PH	110	400	2250	1561	232	416	184
VC.110.400.2300.4PH	110	400	2300	1602	236	423	187
VC.110.400.2350.4PH	110	400	2350	1643	240	432	192
VC.110.400.2400.4PH	110	400	2400	1684	245	440	195
VC.110.400.2450.4PH	110	400	2450	1725	254	454	200
VC.110.400.2500.4PH	110	400	2500	1766	258	461	203
VC.110.400.2550.4PH	110	400	2550	1807	262	470	208
VC.110.400.2600.4PH	110	400	2600	1848	266	478	211
VC.110.400.2650.4PH	110	400	2650	1889	270	486	216
VC.110.400.2700.4PH	110	400	2700	1931	275	494	219
VC.110.400.2750.4PH	110	400	2750	1972	279	502	223
VC.110.400.2800.4PH	110	400	2800	2013	284	511	227
VC.110.400.2850.4PH	110	400	2850	2054	288	518	231
VC.110.400.2900.4PH	110	400	2900	2095	292	527	235
VC.110.400.2950.4PH	110	400	2950	2136	296	535	239
VC.110.400.3000.4PH	110	400	3000	2177	307	550	243

Aukštis: 110 mm.

Plotis: 400 mm.

Šiluminė galia : 205 - 2177 W.

Šilumokaitis: 4 vamzdis, horizontalus

Standartinis ilgis : 600-3000 mm (žingsnis 50 mm)